



Mechanical characteristics

- Aerodynamic coefficient (CxS): KANN 350 : 0.67 m², KANN 450 : 0.86 m², KANN 350 : 1.05 m².
- Protection index: Optical unit IP66.
- Shock resistance: IK10.
- Materials: Body made of aluminium / Protection made of transparent PC treated with UV protection.

Electrical characteristics

- Power current up to 700 mA.
- Voltage range: From 220 V to 240 V.
- Electrical class: II.
- Varistor (protection against surges - offset in the base of the bollard).
- Optional surge protector or over/under voltage protection systems (offset in the base of the bollard).
- Standard electrical shock resistance: 6/10 kV (diff/comm).

LED characteristics

- Type: CMS.
- Luminous flux maintenance: L90 B10 100 000 hrs.
- 3000K/4000K/2700K: CRI >70 - 2200K: CRI >80.
- ULR <1% (ULR: Upward Light Ratio)

Powers and luminous intensities

2200K Number of LED	Nominal flux ⁽¹⁾ (lm)	Nominal eff. ⁽¹⁾ (lm/W)	350 mA			500 mA			700 mA			Energy efficiency class
			P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	
16	3920	144	19	1642	87	26	2252	87	36	3058	85	E

2700K Number of LED	Nominal flux ⁽¹⁾ (lm)	Nominal eff. ⁽¹⁾ (lm/W)	350 mA			500 mA			700 mA			Energy efficiency class
			P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	
16	4550	165	19	1906	101	26	2614	101	36	3549	99	D

3000K Number of LED	Nominal flux ⁽¹⁾ (lm)	Nominal eff. ⁽¹⁾ (lm/W)	350 mA			500 mA			700 mA			Energy efficiency class
			P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	
16	4720	174	19	2005	106	26	2746	106	36	3682	103	D

4000K Number of LED	Nominal flux ⁽¹⁾ (lm)	Nominal eff. ⁽¹⁾ (lm/W)	350 mA			500 mA			700 mA			Energy efficiency class
			P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	P _t (W) ⁽²⁾	Φ (lm) ⁽²⁾	(lm/W) ⁽²⁾	
16	4980	185	19	2114	112	26	2902	112	36	3884	108	D

(1) Maximum LED flux at operating temperature including driver consumption.
(2) Actual luminaire output data at operating temperature including driver consumption, optical accessories. A tolerance on the data is allowed in accordance with IEC 62717 and IEC 62722.

Photometric distributions

ASYMMETRICAL ROAD LIGHTING

