

Cast aluminium or
bronze ornamentation



MONACO

LUMINAIRE'S SPECIFICATIONS

IK08
IP66

Dome made of embossed aluminium, copper or brass

IP68 vent

Luminaire's body

Model	Diameter	Height	Aerodynamic coefficient (CxS)	Weight
Monaco 638	400 mm	739 mm	0.100 m ²	9 kg
Monaco 650	500 mm	950 mm	0.160 m ²	10.5 kg

PROTECTION FINISH
Standard: Transparent
Option: Diffuse white or frosted

Standard color: Dark black RAL 9005

FIXING
Top mounted: on 3/4" BSPT male
Suspended: 3/4" BSPT male

Optical unit & control gear

8 to 64 LED module - From 1000 to 18400 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR < 1% (LED) (ULR: Upward Light Ratio).

Materials	ME (ME Resist on request) or tempered glass
Electric class	I and II
Protection shape	Standard: Cylindro-conic optical unit Option: Flat glass
Protection index	IP66
Shock resistance	IK08 IK10 (on request)

Operating temperature: -40°C to +35°C (up to +50° under conditions).

*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.

Options

- Zhaga socket or Nema socket.
- Blackout face for heritage circular luminaires.

Available in anodized aluminum or painted as per the client's choice.

Available for all heritage luminaires - Adaptation of the plate according to the type and the size of the luminaire (Consult us for the flat glass version).

Used to prevent light pollution to nearby homes and gardens.

Can be setup after the installation of the luminaire.



638



650

