

Cast aluminium or  
bronze ornamentation

# MONACO

YOKE

## LUMINAIRE'S SPECIFICATIONS

IK09  
IP66

Dome made of embossed aluminium, copper or brass

IP68 vent

Luminaire's body

Model	Diameter	Height	Aerodynamic coefficient (C <sub>x</sub> S)	Weight
<b>Monaco 655 on yoke</b>	510 mm	900 mm	0.170 m <sup>2</sup>	12 kg

PROTECTION FINISH  
Standard: Transparent  
Option: Diffuse white or frosted

Standard color: Dark black RAL 9005

Fixing on Ø34 - Depth of insertion: 80 mm

## Optical unit & control gear

8 to 48 LED module - From 1000 to 13800 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR <1% (LED) (ULR: Upward Light Ratio).

**Materials**

ME (ME Resist on request) or tempered glass

**Electric class**

I and II

**Protection shape**

Bowl optical unit

**Protection index**

IP66

**Shock resistance**IK09  
IK10 (on request)

Operating temperature: -40°C to +35°C (up to +50° under conditions).

\*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.

23/04/2025 - All informations are subject to change without notice.





## Options

- Zhaga socket or Nema socket.

