

Standard color
Dark black RAL 9005



OPIO

LUMINAIRE'S SPECIFICATIONS



Machine-welded galvanized steel lyre

Dome made of embossed aluminium, copper or brass

IP68 vent

Luminaire's body

	Model	Diameter	Height	Aerodynamic coefficient (C _x S)	Weight
Opio 640	suspended	490 mm	820 mm	0.110 m²	11 kg
	top-mounted	490 mm	590 mm		
Opio 650	suspended	580 mm	880 mm	0.160 m²	12 kg
	top-mounted	580 mm	770 mm		
Materials	Stainless steel				

PROTECTION FINISH
Standard: Transparent
Option: Diffuse white or frosted

FIXING
Top mounted: on 3/4" BSPT male
Suspended: 3/4" BSPT male

Options

- Zhaga socket or Nema socket.

Optical unit & control gear

8 to 64 LED module - From 1000 to 18400 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR <1% (LED) (ULR: Upward Light Ratio).

Materials	ME (ME Resist on request)
Electric class	I and II
Protection shape	6-sided optical unit
Protection index	IP66
Shock resistance	IK08 IK10 (on request)

Operating temperature: -40°C to +35°C (up to +50° under conditions).

*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.

23/04/2025 - All informations are subject to change without notice.