

FIXATION
Suspended:
3/4" BSPT male



RUBIQ

LUMINAIRE'S SPECIFICATIONS



Stainless steel

IP68 vent

Transparent flat glass

Luminaire's body

Model	Width	Height	Aerodynamic coefficient (C _x S)	Weight
Suspended	325 mm	482 mm	0,087 m ²	6 kg
Top-mounted	325 mm	500 mm	0,078 m ²	5.5 kg

Standard color
Dark black RAL 9005

Tool-free opening



FIXATION
Top-mounted: on 3/4" BSPT male

Optical unit & control gear

8 to 48 LED module - From 1000 to 10300 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR <1% (LED) (ULR: Upward Light Ratio).

Materials	Tempered glass
Electric class	I & II
Protection shape	Flat glass
Protection index	IP66
Shock resistance	IK08

Operating temperature: -40°C to +35°C (up to +50° under conditions).

*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.

23/04/2025 - All informations are subject to change without notice.





Options

- Zhaga or Nema socket on top of the luminaire to connect OLC or photocell. Zhaga socket at the bottom of the luminaire to add accessories such as sensors.
- Stirrup on suspended version



17/12/2024 - All informations are subject to change without notice.