

Standard color
Dark black RAL 9005



VALBONNE

LUMINAIRE'S SPECIFICATIONS



Dome made of embossed aluminium, copper or brass

IP68 vent

Luminaire's body

Model	Diameter	Height	Aerodynamic coefficient (CxS)	Weight
Valbonne 640	430 mm	720 mm	0.100 m ²	12 kg
Valbonne 650	580 mm	750 mm	0.170 m ²	14 kg
Valbonne 665	620 mm	800 mm	0.200 m ²	17 kg
Materials			Stainless steel	

PROTECTION FINISH
Standard: Transparent
Option: Diffuse white or frosted

FIXING
Top mounted: on 3/4" BSPT male
Suspended: 3/4" BSPT male

Options



- Zhaga socket or Nema socket.

Optical unit & control gear

8 to 64 LED module - From 1000 to 18400 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR < 1% (LED) (ULR: Upward Light Ratio).

Materials	ME (ME Resist on request)
Electric class	I and II
Protection shape	Standard: Bowl optical unit Option: Ogive bowl optical unit
Protection index	IP66
Shock resistance	IK09 IK10 (on request)

Operating temperature: -40°C to +35°C (up to +50° under conditions).

*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.



IK09
IP66

Tool free
opening

1000 lm
18400 lm

Zhaga
standard

REASONABLE LIGHTING
COMPLIANT
DECREE
27/12/2018
LIGHT POLLUTION PREVENTION